



ViewSonic Projectors

Award-winning. Innovative. Dependable. ViewSonic brings you the most complete line of performance LCD and DLP® projectors from road-ready portables to models designed for large venues and entertainment. When you're navigating through a forest of projector options, let the visual experts at ViewSonic guide you.

Unmatched Support

ViewSonic has one of the **best product warranties** and **service support** in the business!



3-Year

Parts and labor limited warranty

1-Year

Free Express Exchange® service*

1-Year

Limited lamp warranty

	Entry SVGA				
	PJD5123	PJD5126	PJD5132	PJD5133	PJD5134
Native Resolution	SVGA 800×600	SVGA 800×600	SVGA 800×600	SVGA 800×600	SVGA 800×600
Technology	DLP®	DLP®	DLP®	DLP®	DLP®
Brightness Lumens (max)	2,700	2,700	2,800	2,700	2,800
Contrast Ratio (max)	3000:1	15,000:1††	15,000:1††	3000:1	15,000:1††
Display Size (in.)	27–300	30–300	24–300	27–300	24–300
Aspect Ratio	4:3 (native), 16:9	4:3 (native), 16:9	4:3 (native)	4:3 (native), 16:9	4:3 (native)
Minimum Projection Throw Distance (in.)	47	47	40	47	40
Throw Ratio	1.97–2.17:1	1.86–2.04:1	1.86–2.04:1	1.97–2.17:1	1.86–2.04:1
Digital Keystone Correction	Yes	Yes	Yes	Yes	Yes
Zoom/Focus Control	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Energy Saving/Eco-mode	Yes	Yes	Yes	Yes	Yes
Noise Level (dB) Normal/Eco-mode	32/30	32/29	32/29	32/30	32/29
Lamp Life** (hrs.) Normal/Eco-mode	5,000/6,000	5,000/6,000	4,500/6,000	5,000/6,000	4,500/6,000
Altitude (ft.)	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000
Lamp Type (watts)	180	180	190	180	190
Net Weight (lb.)	5.7	5.7	4.6	5.7	4.6
Integrated Speakers	1x2–watt	1x2–watt	1x2–watt	1x2–watt	1x2–watt
Mac® Compatible***	Yes	Yes	Yes	Yes	Yes
Remote Control/Mouse	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes
Advanced Connect™ Technology	–	–	–	–	–
Optional Dual Interactive Pen	–	–	–	–	–
RGB Inputs/Outputs	2/1	2/1	2/1	2/1	2/1
Additional Inputs	S-video, component (DB-15)†, composite, audio, RS-232	S-video, component (DB-15)†, composite, audio, RS-232	S-video, component (DB-15)†, composite, audio, RS-232	HDMI, S-video, component (DB-15)†, composite, audio, RS-232	HDMI, S-video, component (DB-15)†, composite, audio, RS-232
120Hz/3D Ready	Yes	Yes	Yes	Yes	Yes
Video Compatibility (typ)	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV
Dimensions W x H x D (in.)	11.2 x 3.2 x 9.2	11.6 x 3.3 x 9.5	10.6 x 3.3 x 8.7	11.2 x 3.2 x 9.2	10.6 x 3.3 x 8.7
Power Consumption – watts (typ)	235	243	250	235	250
Includes Soft Case	No	No	No	No	No
Limited Lamp Warranty	1-year	1-year	1-year	1-year	1-year
First-Year Express Exchange®*	FREE	FREE	FREE	FREE	FREE
Limited Warranty	3-year	3-year	3-year	3-year	3-year

Sales: (888) 881-8781 . salesinfo@ViewSonic.com . ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running eco-mode or whisper-mode exclusively can extend lamp life. ***Adapter may be required. Analog adapter available from ViewSonic. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-00B-02/13]

	Entry XGA				Ultra Portable	
	PJD5223	PJD5232	PJD5233	PJD5234	PLED-W200	PLED-W500
Native Resolution	XGA 1024x768	XGA 1024x768	XGA 1024x768	XGA 1024x768	WXGA 1280x800	WXGA 1280x800
Technology	DLP®	DLP®	DLP®	DLP®	LED with DLP®	LED with DLP®
Brightness Lumens (max)	2,700	2,800	2,700	2,800	250	500
Contrast Ratio (max)	3000:1	15,000:1††	3000:1	15,000:1††	2000:1	6000:1
Display Size (in.)	27–300	24–300	27–300	24–300	24–80	30–100
Aspect Ratio	4:3 (native), 16:9	4:3 (native)	4:3 (native), 16:9	4:3 (native)	16:10 (native), 16:9, 4:3	16:10 (native), 16:9, 4:3
Minimum Projection Throw Distance (in.)	47	39	47	39	24	35
Throw Ratio	1.97–2.17:1	1.97–2.17:1	1.97–2.17:1	1.97–2.17:1	1.16:1	1.4:1
Digital Keystone Correction	Yes	Yes	Yes	Yes	Yes, auto vert	Yes, auto vert
Zoom/Focus Control	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Digital/Manual	Digital/Manual
Energy Saving/Eco-mode	Yes	Yes	Yes	Yes	Yes	Yes
Noise Level (dB) Normal/Eco-mode	32/30	32/29	32/30	32/29	< 32	36/32
Lamp Life** (hrs.) Normal/Eco-mode	5,000/6,000	5,000/6,000	5,000/6,000	5,000/6,000	> 20,000	> 20,000
Altitude (ft.)	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000
Lamp Type (watts)	180	190	180	190	LED	LED
Net Weight (lb.)	5.7	4.7	5.7	4.7	0.9	2.6
Integrated Speakers	1x2-watt	1x2-watt	1x2-watt	1x2-watt	2x2-watt	1x2-watt
Mac® Compatible***	Yes	Yes	Yes	Yes	Yes	Yes
Remote Control/Mouse	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/No	Yes/No
Advanced Connect™ Technology	–	–	–	–	–	–
Optional Dual Interactive Pen	–	–	–	–	–	–
RGB Inputs/Outputs	2/1	2/1	2/1	2/1	1/0	1/0
Additional Inputs	S-video, component (DB-15)†, composite, audio, RS-232	S-video, component (DB-15)†, composite, audio x2, RS-232	HDMI, S-video, component (DB-15)†, composite, audio, RS-232	HDMI, S-video, component (DB-15)†, composite, audio x2, RS-232	Component (DB-15)†, composite, audio, USB	HDMI, S-Video Component (DB-15)†, composite, audio, USB, SD, Memory (1GB)
120Hz/3D Ready	Yes	Yes	Yes	Yes	Yes	Yes
Video Compatibility (typ)	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV
Dimensions– W x H x D (in.)	11.2 x 3.2 x 9.2	11.6 x 3.7 x 8.0	11.2 x 3.2 x 9.2	11.6 x 3.7 x 8.0	5.1 x 1.3 x 5.0	5.1 x 1.3 x 5.0
Power Consumption – watts (typ)	235	245	235	245	< 50	< 50
Includes Soft Case	No	No	No	No	Yes	Yes
Limited Lamp Warranty	1-year	1-year	1-year	1-year	N/A	N/A
First-Year Express Exchange®*	FREE	FREE	FREE	FREE	FREE	FREE
Limited Warranty	3-year	3-year	3-year	3-year	3-year	3-year

Sales: (888) 881-8781 . salesinfo@ViewSonic.com . ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running eco-mode or whisper-mode exclusively can extend lamp life. ***Adapter may be required. Analog adapter available from ViewSonic. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-00B-02/13]

	Short Throw			Ultra Short Throw			
	PJD6353s	PJD6383s	PJD6683ws	PJD8333s	PJD8633ws	PJD8353s	PJD8653ws
Native Resolution	XGA 1024x768	XGA 1024x768	WXGA 1280x800	XGA 1024x768	WXGA 1280x800	XGA 1024x768	WXGA 1280x800
Technology	DLP®	DLP®	DLP®	DLP®	DLP®	DLP®	DLP®
Brightness Lumens (max)	2,500	3,000	3,000	3,000	3,000	2,600	2,600
Contrast Ratio (max)	15,000:1††	15,000:1††	15,000:1††	15,000:1††	15,000:1††	15,000:1††	15,000:1††
Display Size (in.)	30–300	30–300	30–300	60–250	60–250	47–150	47–150
Aspect Ratio	4:3 (native), 16:10	4:3 (native), 16:10	16:10 (native), 4:3	4:3 (native)	16:10 (native)	4:3 (native)	16:10 (native)
Minimum Projection Throw Distance (in.)	15	15	12	19	19	20	20
Throw Ratio	0.61:1	0.61:1	0.5:1	0.468:1	0.375:1	0.43:1	0.35:1
Digital Keystone Correction	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Zoom/Focus Control	Digital/Manual	Digital/Manual	Digital/Manual	Digital/Manual	Digital/Manual	Digital/Manual	Digital/Manual
Energy Saving/Eco-mode	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Noise Level (dB) Normal/Eco-mode	32/29	33/29	33/29	34/32	34/32	34/32	34/32
Lamp Life** (hrs.) Normal/Eco-mode	5,000/6,000	3,500/5,000	3,500/5,000	3,500/5,000	3,500/5,000	3,500/5,000	3,500/5,000
Altitude (ft.)	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000
Lamp Type (watts)	180	240	240	240	240	240	240
Net Weight (lb.)	6.6	6.6	6.6	8.0	8.0	16.1	16.1
Integrated Speakers	1x10-watt	1x10-watt	1x10-watt	1x16-watt	1x16-watt	2x8-watt	2x8-watt
Mac® Compatible***	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Remote Control/Mouse	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes
Advanced Connect™ Technology	–	–	–	Yes	Yes	–	–
Optional Dual Interactive Pen	–	–	–	–	–	Yes	Yes
RGB Inputs/Outputs	2/1	2/1	2/1	2/1	2/1	2/1	2/1
Additional Inputs	HDMI, S-video, component (DB-15)†, composite, audio x2, RS-232	HDMI, S-video, component (DB-15)†, composite, audio x2, RS-232	HDMI, S-video, component (DB-15)†, composite, audio x2, RS-232	HDMI, S-video, component (DB-15)†, composite, audio x2, RS-232, RJ45, USB	HDMI, S-video, component (DB-15)†, composite, audio x2, RS-232, RJ45, USB	HDMI, S-video component (DB-15)†, composite, audio x4, RS-232, RJ45, USB	HDMI, S-video component (DB-15)†, composite, audio x4, RS-232, RJ45, USB
120Hz/3D Ready	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Video Compatibility (typ)	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV
Dimensions– W x H x D (in.)	11.6 x 3.3 x 9.5	11.6 x 3.3 x 9.5	11.6 x 3.3 x 9.5	13.2 x 5.1 x 10.4	13.2 x 5.1 x 10.4	14.1 x 9.9 x 14.4	14.1 x 9.9 x 14.4
Power Consumption – watts (typ)	310	310	310	350	350	300	300
Includes Soft Case	No	No	No	Yes	Yes	No	No
Limited Lamp Warranty	1-year	1-year	1-year	1-year	1-year	1-year	1-year
First-Year Express Exchange®*	FREE	FREE	FREE	FREE	FREE	FREE	FREE
Limited Warranty	3-year	3-year	3-year	3-year	3-year	3-year	3-year

Sales: (888) 881-8781 . salesinfo@ViewSonic.com . ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running eco-mode or whisper-mode exclusively can extend lamp life. ***Adapter may be required. Analog adapter available from ViewSonic. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-00B-02/13]



	Business / Education								
	PJD6223	PJD6235	PJD6243	PJD6245	PJD6253	PJD6345	PJD7333	PJL6233	PJL6243
Native Resolution	XGA 1024x768	XGA 1024x768	XGA 1024x768	XGA 1024x768	XGA 1024x768	XGA 1024x768	XGA 1024x768	XGA 1024x768	XGA 1024x768
Technology	DLP®	DLP®	DLP®	DLP®	DLP®	DLP®	DLP®	3LCD	3LCD
Brightness Lumens (max)	2,700	2,800	3,200	3,000	3,500	3,500	4,000	2,600	3,000
Contrast Ratio (max)	15,000:1††	15,000:1††	3000:1	15,000:1††	15,000:1††	15,000:1††	15,000:1††	500:1	4200:1 (with active IRS)
Display Size (in.)	30–300	24–300	30–300	24–300	30–300	28–300	30–300	40–300	40–300
Aspect Ratio	4:3 (native), 16:10	4:3 (native)	4:3 (native), 16:10	4:3 (native)	4:3 (native), 16:10	4:3 (native)	4:3 (native)	4:3 (native), 16:9	4:3 (native), 16:9
Minimum Projection Throw Distance (in.)	47	36	51	36	47	47	47	51	43
Throw Ratio	1.86–2.04:1	1.86–2.04:1	1.64–1.96:1	1.86–2.04:1	1.51–1.97:1	1.97–2.17:1	1.39–2.23:1	1.62–1.92:1	1.43–1.72:1
Digital Keystone Correction	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Zoom/Focus Control	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Energy Saving/Eco-mode	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Noise Level (dB) Normal/Eco-mode	32/27	32/29	34/32	32/29	33/29	34/32	34/32	34/29	34/29
Lamp Life** (hrs.) Normal/Eco-mode	5,000/6,000	4,500/6,000	3,500/5,000	4,500/6,000	3,000/5,000	3,500/5,000	2,500/3,500	4,000/6,000	4,000/6,000
Altitude (ft.)	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000
Lamp Type (watts)	180	190	240	190	240	240	240	215	215
Net Weight (lb.)	5.7	4.6	5.7	4.6	5.7	4.7	6.7	5.7	6.4
Integrated Speakers	1x10-watt	1x2-watt	1x5-watt	1x2-watt	1x10-watt	1x16-watt	1x16-watt	1x1-watt	1x10-watt
Mac® Compatible***	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Remote Control/Mouse	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/No	Yes/No
Advanced Connect™ Technology	–	–	–	–	–	Yes	Yes	–	–
Optional Dual Interactive Pen	–	–	–	–	–	–	–	–	–
RGB Inputs/Outputs	2/1	2/1	2/1	2/1	2/1	2/1	2/1	2/1	2/1
Additional Inputs	HDMI, S-video, component (DB-15)†, composite, audio x2, RJ45, RS-232	HDMI, S-video, component (DB-15)†, composite, audio, RJ45, RS-232	HDMI, S-video, component (DB-15)†, composite, audio, RJ45, RS-232	HDMI, S-video, component (DB-15)†, composite, audio, RJ45, RS-232	HDMI, S-video, component (DB-15)†, composite, audio, RJ45, RS-232	HDMI, S-video, component (DB-15)†, composite, audio x2, RJ45, RS-232, USB	HDMI, S-video, component (DB-15)†, composite, audio x2, RJ45, RS-232, USB	S-video, component (DB-15)†, composite, audio x2, RJ45, RS-232	S-video, component (DB-15)†, composite, audio x2, RJ45, RS-232
120Hz/3D Ready	Yes	Yes	Yes	Yes	Yes	Yes	Yes	No	No
Video Compatibility (typ)	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV
Dimensions– W x H x D (in.)	11.6 x 3.3 x 9.5	10.5 x 3.3 x 8.7	11.2 x 3.5 x 9.2	10.6 x 3.3 x 8.7	11.6 x 3.3 x 9.5	11.6 x 4.5 x 8.6	13.2 x 5.1 x 10.4	13.4 x 4.2 x 9.9	13.4 x 4.6 x 9.9
Power Consumption – watts (typ)	250	240	305	240	310	305	350	284	286
Includes Soft Case	No	No	No	No	No	No	Yes	No	No
Limited Lamp Warranty	1-year	1-year	1-year	1-year	1-year	1-year	1-year	1-year	1-year
First-Year Express Exchange®*	FREE	FREE	FREE	FREE	FREE	FREE	FREE	FREE	FREE
Limited Warranty	3-Year	3-Year	3-Year	3-Year	3-Year	3-Year	3-Year	3-Year	3-Year

Sales: (888) 881-8781 . salesinfo@ViewSonic.com . ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running eco-mode or whisper-mode exclusively can extend lamp life. ***Adapter may be required. Analog adapter available from ViewSonic. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-00B-02/13]

	Installation / Large Venue								
	PJL9371	Pro8200	Pro8300	Pro8400	Pro8450w	Pro8500	Pro8520HD	Pro8600	Pro9000
Native Resolution	XGA 1024x768	Full HD 1920x1080	Full HD 1920x1080	Full HD 1920x1080	WXGA 1280x800	XGA 1024x768	Full HD 1920x1080	XGA 1024x768	Full HD 1920x1080
Technology	3LCD	DLP®	DLP®	DLP®	DLP®	DLP®	DLP®	DLP®	Laser/LED Hybrid w/DLP®
Brightness Lumens (max)	4,000	2,000	3,000	4,000	4,500	5,000	5,000	6,000	1,600
Contrast Ratio (max)	2000:1	4000:1	4000:1	3000:1	4300:1	4900:1	8000:1	15,000:1††	100,000:1
Display Size (in.)	30–300	30–300	30–300	30–300	30–350	30–300	30–300	30–300	38–150
Aspect Ratio	4:3 (native), 16:9	16:9 (native), 4:3, 16:10	16:9 (native), 4:3, 16:10	16:9 (native), 4:3, 16:10	16:10 (native), 16:9, 4:3	4:3 (native), 16:9, 16:10	16:9 (native)	4:3 (native)	16:9 (native), 4:3
Minimum Projection Throw Distance (in.)	35	36	36	36	47	47	36	36	59
Throw Ratio	1.5–1.8:1	1.4–2.14:1	1.4–2.14:1	1.4–2.14:1	1.46–2.2:1	1.45–2.18:1	1.41–2.14:1	1.45–2.18:1	1.5–1.8:1
Digital Keystone Correction	Yes, auto vert	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Zoom/Focus Control	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Energy Saving/Eco–mode	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Noise Level (dB) Normal/Eco–mode	36/29	31/27	31/27	33/29	32/27	32/27	34/32	34/32	33/28
Lamp Life** (hrs.) Normal/Eco–mode	3,000/5,000	4,000/6,000	4,000/6,000	4,000/5,000	4,000/5,000	4,000/5,000	2,500/3,000	2,500/3,000	>20,000
Altitude (ft.)	0–12,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–6,000
Lamp Type (watts)	260	230	230	280	280	280	350	350	Laser/LED Hybrid
Net Weight (lb.)	9.5	8.5	8.5	8.5	8.6	8.5	8.5	8.5	9.4
Integrated Speakers	2x8–watt	2x10–watt	2x10–watt	2x10–watt	2x10–watt	2x10–watt	2x10–watt	2x10–watt	2x2–watt
Mac® Compatible***	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Remote Control/Mouse	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/No
Advanced Connect™ Technology	–	–	–	–	–	–	–	–	–
Optional Dual Interactive Pen	–	–	–	–	–	–	–	–	–
RGB Inputs/Outputs	2/1	2/1	2/1	2/1	2/1	2/1	2/1	2/1	1/0
Additional Inputs	S–video, component (DB–15)† composite, audio x2, RS–232	HDMI x2, S–video, component (DB–15)† composite, audio x3, RS–232	HDMI x2, S–video, component (DB–15)† composite, audio x3, RS–232	HDMI x2, S–video, component (DB–15)† composite, audio x3, RJ45, USB, RS–232	HDMI, S–video, component (DB–15)† composite, audio x3, RJ45, USB, RS–232	HDMI, S–video, component (DB–15)† composite, audio x3, RJ45, USB, RS–232	HDMI x2, S–video, component (DB–15)† composite, audio x3, RJ45, USB, RS–232	HDMI, S–video, component (DB–15)† composite, audio x3, RJ45, USB, RS–232	HDMI x2, S–Video, component (DB–15)†, composite, audio, RS–232
120Hz/3D Ready	No	No	No	No	Yes	Yes	Yes	Yes	No
Video Compatibility (typ)	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV
Dimensions– W x H x D (in.)	9.5 x 3.9 x 12.5	13.0 x 4.3 x 10.4	13.1 x 4.3 x 10.4	13.0 x 4.8 x 10.4	13.1 x 4.8 x 10.4	13.1 x 4.8 x 10.4	13.1 x 4.8 x 10.4	13.1 x 4.3 x 10.4	12.6 x 5.3 x 10.2
Power Consumption – watts (typ)	390	310	310	360	350	350	450	408	<186
Includes Soft Case	No	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Limited Lamp Warranty	1–year	1–year	1–year	1–year	1–year	1–year	1–year	1–year	N/A
First–Year Express Exchange®**	FREE	FREE	FREE	FREE	FREE	FREE	FREE	FREE	FREE
Limited Warranty	3–Year	3–Year	3–Year	3–Year	3–Year	3–Year	3–Year	3–Year	3–Year

Sales: (888) 881–8781 . salesinfo@ViewSonic.com . ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running eco–mode or whisper–mode exclusively can extend lamp life. ***Adapter may be required. Analog adapter available from ViewSonic. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565–00B–02/13]

Wide Format

	PJD5533w	PJD6543w	PJD6553w	PJD6544w	PJD7533w	PJD7820HD
Native Resolution	WXGA 1280x800	WXGA 1280x800	WXGA 1280x800	WXGA 1280x800	WXGA 1280x800	Full HD 1920x1080
Technology	DLP®	DLP®	DLP®	DLP®	DLP®	DLP®
Brightness Lumens (max)	2,800	3,000	3,500	3,500	4,000	3,000
Contrast Ratio (max)	15,000:1††	15,000:1††	15,000:1††	15,000:1††	15,000:1††	15,000:1††
Display Size (in.)	28–300	28–300	30–300	28–300	30–300	30–300
Aspect Ratio	16:10 (native)	16:10 (native)	16:10 (native), 4:3	16:10 (native)	16:10 (native)	16:10 (native)
Minimum Projection Throw Distance (in.)	39	36	47	47	47	30
Throw Ratio	1.5–1.65:1	1.5–1.65:1	1.21–1.57:1	1.47–1.83:1	1.47–1.83:1	1.15–1.5:1
Digital Keystone Correction	Yes	Yes	Yes	Yes	Yes	Yes
Zoom/Focus Control	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual	Manual/Manual
Energy Saving/Eco-mode	Yes	Yes	Yes	Yes	Yes	Yes
Noise Level (dB) Normal/Eco-mode	33/29	32/29	33/29	34/32	34/32	35/29
Lamp Life** (hrs.) Normal/Eco-mode	5,000/6,000	4,500/6,000	3,500/5,000	3,500/5,000	2,000/3,500	4,000/6,000
Altitude (ft.)	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000	0–10,000
Lamp Type (watts)	190	190	240	240	330	210
Net Weight (lb.)	4.6	4.6	5.7	4.7	5.7	4.6
Integrated Speakers	1x2–watt	1x2–watt	1x10–watt	1x16–watt	1x16–watt	1x2–watt
Mac® Compatible***	Yes	Yes	Yes	Yes	Yes	Yes
Remote Control/Mouse	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes	Yes/Yes
Advanced Connect™ Technology	–	–	–	Yes	Yes	–
Optional Dual Interactive Pen	–	–	–	–	–	–
RGB Inputs/Outputs	2/1	2/1	2/1	2/1	2/1	2/1
Additional Inputs	HDMI, S-video, component (DB-15)†, composite, audio, RS-232	HDMI, S-video, component (DB-15)†, composite, audio, RJ45, RS-232	HDMI, S-video, component (DB-15)†, composite, audio x2, RJ45, RS-232	HDMI, S-video, component (DB-15)†, composite, audio x2, RJ45, RS-232, USB	HDMI, S-video, component (DB-15)†, composite, audio x2, RJ45, RS-232, USB	HDMI, S-video, component (DB-15)†, composite, audio, RS-232
120Hz/3D Ready	Yes	Yes	Yes	Yes	Yes	Yes
Video Compatibility (typ)	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV	NTSC, PAL, SECAM, HDTV
Dimensions– W x H x D (in.)	10.6 x 3.3 x 8.7	10.6 x 3.3 x 8.7	11.6 x 3.3 x 9.5	11.6 x 4.5 x 8.6	13.2 x 5.1 x 10.4	10.6 x 3.3 x 8.7
Power Consumption – watts (typ)	240	240	310	305	350	260
Includes Soft Case	No	No	No	No	Yes	No
Limited Lamp Warranty	1–year	1–year	1–year	1–year	1–year	1–year
First-Year Express Exchange®**	FREE	FREE	FREE	FREE	FREE	FREE
Limited Warranty	3–year	3–year	3–year	3–Year	3–Year	3–Year



Projector Replacement Lamps

ViewSonic offers longlife, user-installable replacement lamps for all our projectors.

Model #	Lamp for:	Model #	Lamp for:	Model #	Lamp for:
RLC-025	PJ258D	RLC-055	PJD5122 PJD5352 PJD5352	RLC-075	PJD6243
RLC-026	PJ588D			RLC-076	Pro8520HD Pro8600
RLC-027	PJ358			RLC-077	PJD5226
RLC-030	PJ503D				
RLC-031	PJ759	RLC-057	PJD7382 PJD7383 PJD7583w PJD7383i PJD7583wi	RLC-078	PJD5132 PJD5134 PJD6235 PJD6245
RLC-033	PJ260D				
	PJ551D PJ557D PJD6220	RLC-059	Pro8450w Pro8500 Pro8400	RLC-079	PJD7820HD
RLC-037	PJ560D PJ6240			RLC-080	PJD8333s PJD8633ws
RLC-038	PJ1173	RLC-061	Pro8200 Prp8300	RLC-081	PJD7533w PJD7333
RLC-039	PJ359w PJL3211	RLC-063	Pro9500		
RLC-047	PJD5351	RLC-065	PJL6233 PJD6243	RLC-082	PJD8353s PJD8653ws
RLC-049	PJD6381 PJD6241 PJD6531w	RLC-070	PJD5126 PJD6223 PJD6353s	RLC-083	PJD5232 PJD5234
RLC-050	PJD6211 PJD6221 PJD6531w	RLC-071	PJD6253 PJD6553w PJD6383s PJD6683ws	RLC-084	PJD6544w PJD6345
RLC-051	PJD6251			RLC-085	PJD5533w PJD6543w
RLC-052	PJD2121	RLC-072	PJD5123 PJD5133 PJD5223 PJD5233 PJD5523w		
RLC-053	PJL9371				
RLC-054	PJL7211				

Projector Mounts and Accessories

Model #	Description
WMK-005	Universal ceiling mount (not compatible with 2 lb. projectors)
WMK-027	Short throw wall mount (short throw and interactive short throw projectors)
WMK-042	Ultra short throw wall mount (ultra short throw projectors)
PJ-PEN-003	Interactive Pen / Camera Kit (for PJD8353s, PJD8653ws)
WPD-100	Wireless USB adapter (for wireless presentations)

Visit ViewSonic.com for a full list of projector accessories.

Sales: (888) 881-8781 . salesinfo@ViewSonic.com . ViewSonic.com

*First year Free Express Exchange® Service requires product registration. **Running eco-mode or whisper-mode exclusively can extend lamp life. ***Adapter may be required. Analog adapter available from ViewSonic. †Optional RGB to component video adapter required. †† With DynamicEco™. For the most current product accessories and specifications, visit ViewSonic.com. DLP is a registered trademark of Texas Instruments, Inc. in the United States and/or other countries. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2013 ViewSonic Corporation. All rights reserved. [16565-00B-02/13]